

SAUNA STAIN– wood stain

SAFETY DATA SHEET

Prepared according to the requirements of § 31 of Regulation (EC) 1907/2006 (REACH)

Date 8 December 2013

Review date: 28 October 2015

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Identification of the substance/mixture

Commercial name of the product

SAUNA STAIN– wood stain

Product identification code

SPM/SPT

1.2 Identification of the company/undertaking

1.2.1 Manufacturer, importer, etc.

Supplier:

Amello Grupp OÜ

Mustamäe tee 16

10617 TALLINN

+ 372 6 720 471

+372 6 720 455

info@amello.ee

1.2.2 Postal address

Postal code and institution

Telephone

Fax

e-mail

1.2.3 Emergency phone number

General emergency number: 112

Poisoning Information Centre: 16662

2. HAZARDS IDENTIFICATION

2.1. Classification of the substance/mixture:

Classification according to Regulation (EC) No 1272/2008 (CLP)

According to Regulation (EC) No 1272/2008, the product has been classified as hazardous.

Flammable liquids, hazard class 2; H225

Eye irritation, hazard class 2; H319

Acute Toxic, hazard class 4; H332

Full texts of the above listed risk and safety phrases are provided in point 16. More detailed information about the health impacts and symptoms is provided in points 11 and 12.

2.2 Information on labelling



Marker word: CAUTION!

Floor Oil– wood care

Date 8 December 2013

Review date:

Hazard phrases:

H225 Highly flammable liquid and vapour
H319 Causes serious eye irritation
H332 Harmful if inhaled

Precautionary phrases:

P102 Keep out of reach of children
P280 Wear protective gloves
P210 Keep away from heat/sparks/open flames/hot surfaces. – No smoking
P403 Store in a well-ventilated place

Names of the components on the label

-

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Hazardous ingredients

3.1.1 CAS No	3.1.2 Name of the substance	3.1.3 Concentration	3.1.4	3.1.5 Classification (EC) 1272/2008 [CLP]	3.1.6 Type
64-17-5	Ethanol	25-50%	F, R11	Flam. Liq. 2; H225	[1] [2]
107-98-2	1-methoxy-2- propanol	25-50%	R10	Flam. Liq. 3; H226	[1] [2]
67-63-0	Isopropanol	10-25%	F, Xi, R11,R36,R3 7	Flam. Liq. 2; H225 Skin Irrit. 2; H319 Acute Tox. 4 ; H332	[1] [2]

Full texts of the above listed risk and safety phrases are provided in point 16.

Type

[1] Substance has been classified as hazardous to health or environment.

[2] Substance for which an occupational exposure limit has been established.

[3] Substance that corresponds to the PBT (persistent, liable to bioaccumulate and toxic) requirements of Appendix 13 of Regulation (EC) No 1907/2006.

[4] Substance that corresponds to the vPvB (very persistent, very liable to bioaccumulate) requirements of Appendix 13 of Regulation (EC) No 1907/2006.

4. FIRST AID MEASURES

4.1 Specific instructions

Highly flammable

4.2 Inhalation

Floor Oil– wood care

Date 8 December 2013

Review date:

Inhalation: Take victim to fresh air, to a quiet place and keep him/her warm. Provide CPR if necessary and get medical attention.

4.3 Skin contact

Skin contact: Remove contaminated clothes. Wash off with soap and plenty of water. Use skin cream. In case of an emergency wipe with a solvent impregnated cloth or cleaning emulsion.

4.4 Eye contact

Eye contact: Rinse immediately with plenty of water for at least 15 minutes. See a doctor if necessary.

4.5 If swallowed

When swallowed down: Do not induce vomiting. Rinse mouth and drink water or milk. Get medical attention if necessary.

5. FIREFIGHTING MEASURES

5.1 Appropriate firefighting means

Put out the fire with a foam, powder or carbon dioxide (CO₂) fire-extinguisher

5.2 Firefighting means that are hazardous to use

Do not use water (when putting out the fire)

5.3 Specific risks of firefighting

Avoid inhalation of smoke coming from the fire

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal protective gear and behaviour in an emergency

See points 7 and 8.

6.2 Environment protection measures

Do not pour on ground or into sewerage

6.3 Pollution control measures

Cleaning: let it absorb into peat or sawdust and collect all waste.

7. HANDLING AND STORAGE

7.2 Handling

- 1.1.1. ensure adequate ventilation
- 1.1.2. do not smoke
- 1.1.3. keep containers tightly closed
- 1.1.4. obstruct the sparks of statical electricity
- 1.1.5. avoid contact with eyes and skin

7.2 Storage

Well ventilated and dry storage

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ensure adequate ventilation

- 1.2. Eye protection: protective glasses
- 1.3. Skin and body protection: protective gloves, protective clothes
- 1.4. Hand protection: rubber gloves

Respiratory protection: in case of inadequate ventilation use protective equipment

9. PHYSICAL AND CHEMICAL PROPERTIES

- 1.1. Appearance, colour, odour: liquid
- 1.2. Boiling point/range: 82 °C
- 1.3. Flash point: 16 °C
- 1.4. Density: 850 kg/ m³ (20 °C)
- 1.5. Water solubility: insoluble

Fat solubility: not applicable

10. STABILITY AND REACTIVITY

At normal conditions the liquid is stable.

- 1.5. Keep away from acid
- 1.6. Avoid certain plastics which are soluble in product.

On higher temperature and on burning process exhale harmful products.

11. TOXICOLOGICAL INFORMATION

- 11.2 acute toxic ---
- 11.3 irritating, corrosive.
- 11.4 may cause allergy
- 11.5 inhalation may cause headache.

12. ECOLOGICAL INFORMATION

12.5 Other data

Paint products must be handled with care, they can not get into surface, drain or water

13. DISPOSAL CONSIDERATIONS

- 13.1 Collect all waste and destroy according to waste management program.
- 13.2 Empty and dry packages can be taken into the waste or disposed according to local legislation.

14. TRANSPORT INFORMATION

Transport

- | | |
|--------------------------------|---------------|
| 14.1 UN number | 1263 |
| 14.3 Road transport | III |
| 14.3.1 Transport class VAK/ADR | ADR/RID 3.5 B |
| 14.4 Maritime transport | 3.2 |

15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legal acts applied to the substances and mixtures

Floor Oil– wood care

Date 8 December 2013

Review date:

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the registration, evaluation, authorisation and restriction of chemicals (REACH).

Commission Regulation (EU) No 453/2010 of 20 May 2010 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 concerning the classification, labelling and packaging of chemicals (CLP).

Chemicals Act (RT I 1998, 47, 697).

Regulation No 293 of 18 September 2001 of the Government of the Republic "Limit values for chemical hazards in the working environment".

Waste Act (RT I 2004, 9, 52).

Regulation No 102 of 6 April 2004 of the Government of the Republic "List of waste, including hazardous waste".

Regulation No 118 of 14 December 2001 of the Minister of Transport and Communications "Road transport regulation of dangerous goods".

15.2 Chemical safety assessment

Chemical safety has not been assessed.

16. OTHER INFORMATION

16.1 The meanings of risk/hazard phrases and classifications (CLP) provided in point 3 have been listed below:

Full texts of hazard phrases:

H225 Highly flammable liquid and vapour

H319 Causes serious eye irritation

H332 Harmful if inhaled

Full texts of CLP classification hazard classes:

Flammable liquids, hazard class 2; H225

Eye irritation, hazard class 2; H319

Acute Tox. 4, 4.hazard class; H332

16.2 Intended usage

16.1.1 Expressed in words

Wood stain

16.1.2 Usage code

16.3 User manual

Detailed instructions on the product label and product manual.

16.4 Other data

-

16.5 Additional information

Amello Grupp OÜ +372 6 720 471